

DECLARATION OF CONFORMITY

Compatibility for all A2L and A3 flammable refrigerants

TYPE OF EQUIPMENT:

Spark Free Combustible Gas Recovery Machines

Mastercool recovery machines 69390, 69395 and 69400 are approved to be used in an environment where flammable gases are not normally present. That is to recover the refrigerant in a sealed air conditioning system to a sealed cylinder designated for recovered refrigerant in a well ventilated area.

MODEL NUMBER(S):

69390, 69390-220, 69395, 69395-220, 69400, 69400-220

	69390, 69395	69390-220, 69395-220	69400	69400-220
Operating Voltage	115 V	220 V	115 V	220 V
Frequency	60 Hz	50/60 Hz	60 Hz	50/60 Hz
Motor Power	1/2 HP	1/2 HP	1/2 HP	1/2 HP
Operating Temperature	32 to 122°F	32 to 122°F	32 to 122°F	32 to 122°F
Safety High Pressure Switch	Yes	Yes	Yes	Yes
Dimensions	18" x 10" x 14"	18" x 10" x 14"	12" x 8" x 11"	12" x 8" x 11"

THIS DECLARATION CONFIRMS THE ABOVE EQUIPMENT HAS BEEN CERTIFIED BY:

- ETL to meet UL 1963 Issued: 2011/06/01 Ed: 4 Rev: 2013/10/11 Refrigerant Recovery/ Recycling Equipment suitable for use with R-134a, R-1234yf, R-32, R-290 (propane), R-600 (butane) and contaminated refrigerants in A/C systems
- Intertek to meet SAE J2851 - FEB2015 Recovery Equipment for Contaminated R-134a or R-1234yf Refrigerant from Mobile Automotive Air Conditioning Systems

MANUFACTURER'S NAME:

Mastercool Inc., One Aspen Drive, Randolph, NJ 07869 USA

I, the undersigned, hereby declare that the equipment specified above conforms to the above Standard(s).

Place: One Aspen Drive
Randolph, NJ 07869

Signature:



Full Name: Idean Barjesteh

Date: February 8, 2022

Position: International Sales Manager



Mastercool[®]
"World Class Quality"